TECHNICAL.NEWS

How To Put Fexibility Into The Manufacturing Process

Industrial Indexing Systems, Inc

Conventional packaging equipment may not provide a simple way to handle product size variations quickly, resulting in unproductive setup times.

The solution is flexibility. The core of flexibility lies in the underlining capability of the automation system. Its functionality and the speed to execute it are crucial for the repetition rates needed in today's manufacturing equipment. Operations include:

- Controlling web tension
- Printing multiple colors
- Registering for die-cutting
- Applying glue spots on the fly
- Die-cutting finished products
- Forming finished products

Synchronized motion of material, forming processes, and coordinated electrical and servo actuated systems to punch, seal, cut, glue, stack, and wrap give flexibility. Different sized products requiring unique settings are accommodated quickly by selecting from a library of recipes on the screen. Make needed adjustments on the operator's terminal to suit the process, and you can save them for future product runs.

How does the controller achieve this functionality? Comparing a mechanical similarity forms a good picture of what is happening in the realm of software. The software configures and reconfigures actions that are allowed by design to perform. These various actions are programmed to duplicate many mechanical efforts with sequences from the controller's library of functionality.

The examples in (*Figure 1*) illustrate some of the software functions available on all IIS controllers as functional block commands.

Common to all blocks are the Source Position representing a rotating input value such as a motor, an encoder, resolver, or a software-generated 'pseudo motor.' The Lock Control engaging or disengaging the function, and the Lock Method controlling how and when it will engage or disengage, are similar to a clutching method.



Software functions include setting gear ratios, executing CAM tables, and controlling Programmable "limit" Switches. Multiple functions can be instigated, enabled, and executed at the same time in the controller.

Gear Ratio Function

Ratio values range between 0.0001 to 10000. Any motor on the drive network can use output B (*Figure 1*) as its source. This locking method is available to perfectly sync two shafts together recording A's position and accelerating B enough to catch up before locking. For web tension using two motors, connect one pseudo-motor as a source to both motors through separate gear ratio functions. Then, apply a small ratio difference between both to cause and control the tension.

Electronic CAM Function

Continuous positioning of a motor axis along a path using a table of data simulating the function of a mechanical cam. The Source Position addresses the electronic CAM table using linear interpolation between data points for smooth transitions. Using three electronic cam tables on three servomotors will create a three-dimensional path. Multiple cam tables can be switched in and out with smooth transitioning in real-time.

Programmable Output Function

Two main functions in this block feature:

- Synchronizing a digital output to turn on and turn off at positions along a path.
- Turning multiple digital outputs on and off based on time.

Unproductive setup times are reduced by providing flexibility using advanced software functions.

Author Christopher Englert, Director of Sales & Marketing. Industrial Indexings Systems Inc., Victor, N.Y

Copyrighted © 2021 by Industrial Indexing Systems, Inc. Victor, N.Y

Call us today at (585) 924-9181 to discuss how we can help with your application needs

626 Fishers Run, Victor, NY. 14564 ~ info@iis-servo.com ~ www.iis-servo.com

INDUSTRIAL INDEXING SYSTEMS, INC

626 Fishers Run, Victor, NY. 14564 ~ (585) 924-9181 info@iis-servo.com ~ www.iis-servo.com



The IIS Team



Discover how our advanced motion control components and superior support can redefine your operations. Let's embark on a journey to operational excellence. Ready to elevate the efficiency, consistency, and repeatability in your operations? Call us today at (585)924-9181 to discuss your application.



Headquarters in Victor NY

Our location houses all critical departments: Applications Engineering, R&D, Production, Warehouse, Panel Shop, Quality Control, Sales, Marketing, and Customer Support. Having everything under one roof speeds communications and provides better service to our customers.

Check out our IIS InMotion Blog for the Servo Motion Control Professional ~ https://www.iis-servo.com/blog/



for Industrial Indexing Systems, where you'll play a crucial role in boosting brand recognition and nurturing client connections, contact our offices: (585) 924-9181 ~ Email: sales@iis-servo.com EtherCATA DeviceNet BeviceNet B

Copyright Clause: All materials are copyrighted. Users can NOT make changes to digital files, rewrite articles or use our materials without proper permission. Emerald, Emerald Automation Controllers, Emerald Servo Drives, Emerald Series, EMC-2005, Emerald Motion language, EML, Emerald Development Environment, EDE, EMax Positioner Drive, Luminary Motion/Control, Luminary Servo Drives, Luminary Stepper Motor and Drives, and Luminary Series. DeviceNet is a trademark of the Open DeviceNet Vendors Association. SERCOS is a trademark of SERCOS N.A. Windows is a trademark of Microsoft Corporation. CC-Line is a trademark of CC-Link Partner Association. Ethernet is a trade mark of XEROX. Velconic and Toshiba are trademarks of Shibaura Machine. This data is subject to change without notice. © Copyright Industrial Indexing Systems, Inc, 2021